

呼び径	ねじ山				基準径		
	ねじ山数 (25.4mmにつき) n	ピッチ p	山の高さ h	丸み r	おねじ		
					外径 d	有効径 d2	谷の径 d1
					めねじ		
					谷の径 D	有効径 D2	内径 D1
R 1/16	28	0.9071	0.581	0.12	7.723	7.142	6.561
R 1/8	28	0.9071	0.581	0.12	9.728	9.147	8.566
R 1/4	19	1.3368	0.856	0.18	13.157	12.301	11.445
R 3/8	19	1.3368	0.856	0.18	16.662	15.806	14.95
R 1/2	14	1.8143	1.162	0.25	20.955	19.793	18.631
R 3/4	14	1.8143	1.162	0.25	26.441	25.279	24.117
R1	11	2.3091	1.479	0.32	33.249	31.77	30.291
R1 1/4	11	2.3091	1.479	0.32	41.91	40.431	38.952
R1 1/2	11	2.3091	1.479	0.32	47.803	46.324	44.845
R2	11	2.3091	1.479	0.32	59.614	58.135	56.656
R2 1/2	11	2.3091	1.479	0.32	75.184	73.705	72.226
R3	11	2.3091	1.479	0.32	87.884	86.405	84.926
R4	11	2.3091	1.479	0.32	113.03	111.551	110.072
R5	11	2.3091	1.479	0.32	138.43	136.951	135.472
R6	11	2.3091	1.479	0.32	163.83	162.351	160.872